

10/600,065

AF01169/AMDP975US

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions of claims in the application:

Listing of Claims:

1. (Currently amended) An architecture that facilitates a reference voltage in a multi-bit memory, comprising:
 - a multi-bit memory core including a plurality of data cells for storing data;
 - first and second reference arrays of a plurality of multi-bit reference cells fabricated on the memory core, the first and second reference arrays including corresponding reference cells that are interweaved among the plurality of data cells, pairs of the plurality of the multi-bit reference cells each associated with separate wordlines within the multi-bit memory core; and
 - a first bit value of a first reference cell of the first reference array averaged with a second bit value of a second reference cell of the second reference array to arrive at the reference voltage employed during a data cell read operation.
2. (Original) The architecture of claim 1, the core further comprising a sector of multi-bit data cells organized in rows and columns with associated wordlines attached to the multi-bit data cells in a row and with associated bitlines attached to the multi-bit data cells in a column, the first and second reference cells forming a multi-bit reference pair that is programmed and erased with the multi-bit data cells during programming and erase cycles.
3. (Original) The architecture of claim 2, the multi-bit reference pair is associated with a word in a wordline, the multi-bit reference pair utilized during reading of bits of the word.
4. (Original) The architecture of claim 2, the multi-bit reference pair is associated with multi-bit data cells in a wordline, the multi-bit reference pair utilized during reading of bits in the wordline.

10/600,065

AF01169/AMDP975US

5. (Cancelled)
6. (Original) The architecture of claim 2, the multi-bit reference pair is associated with multi-bit data cells in the sector, the multi-bit reference pair utilized during reading of bits in the sector.
7. (Original) The architecture of claim 1, the memory core including a plurality of data sectors that are accessible by the first and second reference arrays, the first and second reference arrays located centrally of the plurality of data sectors.
8. (Original) An integrated circuit comprising the memory of claim 1.
9. (Original) A computer comprising the memory of claim 1.
10. (Original) An electronic device comprising the memory of claim 1.
11. (Cancelled)
12. (Original) The architecture of claim 1, the memory core further comprising a plurality of data sectors, such that each data sector is associated with at least one of the first reference array and the second reference array of multi-bit reference cells.

10/600,065

AF01169/AMDP975US

13. (Currently amended) An architecture that facilitates a reference voltage in a multi-bit memory, comprising:

a multi-bit memory core for storing data, the memory core including two groups of data sectors;

first and second reference arrays of a plurality of multi-bit reference cells fabricated on the memory core interstitial to the groups of data sectors, pairs of the plurality of [[the]] multi-bit reference [[pairs]] cells each associated with a disparate wordline within the two groups of data sectors; and

a first bit value of a first reference cell of the first reference array and a second bit value of a second reference cell of the second reference array forming a reference pair whose respective bit values are averaged to arrive at the reference voltage for a read operation.

14. (Original) The architecture of claim 13, the groups of data sectors read in an interleaved manner with a selected reference pair.

15. (Original) The architecture of claim 13, the first and second reference arrays precharged before being averaged.

16. (Original) The architecture of claim 13, further comprising a redundancy array located at least one of proximate and adjacent to the groups of data sectors.

10/600,065

AF01169/AMDP975US

17. (Currently amended) A method for providing a reference voltage in a multi-bit memory, comprising:

receiving a multi-bit memory core for storing data;

providing first and second reference arrays of a plurality of multi-bit reference cells, ~~the first and second reference arrays~~ the first and second reference arrays including corresponding reference cells that are interweaved among data cells in the multi-bit memory core;

associating ~~each of pairs of~~ each of the plurality of multi-bit reference cells ~~[[pairs]]~~ each with separate wordlines within the memory core; and

averaging a first bit value of a first reference cell of the first reference array with a second bit value of a second reference cell of the second reference array to arrive at the reference voltage utilized during a read operation.

18. (Previously Presented) The method of claim 17, the core comprising a sector of multi-bit data cells organized in rows and columns with associated wordlines attached to the multi-bit data cells in a row and with associated bitlines attached to the multi-bit data cells in a column, the multi-bit reference pairs are programmed and erased with the multi-bit data cells during programming and erase cycles.

19. (Original) The method of claim 18, the multi-bit reference pair is associated with a word in a wordline, the multi-bit reference pair utilized during reading of bits in the word.

20. (Original) The method of claim 18, the multi-bit reference pair is associated with multi-bit data cells in a wordline, the multi-bit reference pair utilized during reading of bits in the wordline.

21. (Previously Presented) The method of claim 18, the associated multi-bit reference pair utilized during reading of bits in the corresponding wordline.

22. (Original) The method of claim 18, the multi-bit reference pair is associated with multi-bit data cells in the sector, the multi-bit reference pair utilized during reading of bits in the sector.

10/600,065

AF01169/AMDP975US

23. (Original) The method of claim 17, the memory core including a plurality of data sectors that are accessible by the first and second reference arrays, the first and second reference arrays located centrally of the plurality of data sectors.

24. (Previously Presented) A system for providing a reference voltage in a multi-bit memory, comprising:

means for providing a multi-bit memory core for storing data;

means for providing first and second reference arrays of a plurality of multi-bit reference cells, the first and second reference arrays including corresponding reference cells that are interweaved among data cells within the multi-bit memory core, the first and second reference arrays fabricated on the memory core; and

means for averaging a first bit value of a first reference cell of the first reference array with a second bit value of a second reference cell of the second reference array to arrive at the reference voltage to facilitate a read operation; and

means for separately monitoring process variations at each wordline within the multi-bit memory core.

25. (Cancelled)

26. (Previously presented) The system of claim 24, the memory core further comprising a plurality of data sectors, such that each data sector is associated with at least one of the first reference array and the second reference array of multi-bit reference cells.

27. (Previously presented) The system of claim 24, further comprising a redundancy array located at least one of proximate and adjacent to the groups of data sectors.